

OUTPUTS STRADA HYBRID

HEIGHT 035

DIMENSIONS			POSITION	HEATING Room temperature 20°C				COOLING Room temperature 27°C	SOUND PRESSURE	ELECTRIC POWER CONSUMPTION	PRICE Standard colours	PRICE Other colours	ORDER CODE			
H	L	B		75/65	55/45	45/35	35/30	16/18								
cm	cm	cm		Watts	Watts	Watts	Watts	Watts	dB(A)	W	€	€				
035	060	11	1	1142	647	409	246	191	26,0	4,8	724	837	STRW.035 060 11 /133 /ACO			
			2	1223	693	438	263	205	30,0	5,4						
			3	1447	819	518	311	242	40,0	6,8						
		16	1	1400	793	501	301	214	26,0	4,8				800	913	STRW.035 060 16 /133 /ACO
			2	1503	851	538	323	230	30,0	5,5						
			3	1989	1126	712	428	305	41,1	7,2						
	080	11	1	1648	933	589	355	276	26,0	6,3	819	932	STRW.035 080 11 /133 /ACO			
			2	1770	1002	633	381	296	30,0	6,8						
			3	2136	1210	764	460	358	41,8	9,1						
		16	1	2040	1156	730	439	312	26,0	6,0				921	1034	STRW.035 080 16 /133 /ACO
			2	2188	1239	783	471	335	30,0	6,7						
			3	2936	1663	1050	632	450	42,4	9,0						
	100	11	1	2136	1210	764	460	358	26,0	7,8	965	1144	STRW.035 100 11 /133 /ACO			
			2	2301	1303	823	495	385	30,0	8,7						
			3	2825	1600	1011	608	473	43,0	12,2						
		16	1	2630	1490	941	566	403	26,0	7,0				1111	1291	STRW.035 100 16 /133 /ACO
			2	2817	1595	1008	606	431	30,0	7,7						
			3	3883	2199	1389	836	595	44,1	10,7						
	120	11	1	2612	1479	935	562	437	26,0	8,9	1061	1241	STRW.035 120 11 /133 /ACO			
			2	2822	1598	1010	607	473	30,0	9,9						
			3	3514	1990	1257	756	589	44,0	14,8						
		16	1	3242	1836	1160	698	496	26,0	8,7				1227	1407	STRW.035 120 16 /133 /ACO
			2	3472	1966	1242	747	532	30,0	9,8						
			3	4830	2735	1728	1039	740	44,8	14,3						
140	11	1	3077	1743	1101	662	515	26,0	10,1	1156	1335	STRW.035 140 11 /133 /ACO				
		2	3333	1887	1192	717	558	30,0	11,2							
		3	4203	2380	1504	904	704	44,8	17,5							
	16	1	3844	2177	1376	827	589	26,0	9,6				1338	1518	STRW.035 140 16 /133 /ACO	
		2	4117	2332	1473	886	630	30,0	10,5							
		3	5777	3272	2067	1243	885	45,4	14,4							
160	11	1	3533	2001	1264	760	592	26,0	11,0	1405	1584	STRW.035 160 11 /133 /ACO				
		2	3835	2172	1372	825	642	30,0	12,4							
		3	4892	2771	1750	1053	819	45,5	19,2							
	16	1	4418	2502	1581	951	676	26,0	11,5				1648	1827	STRW.035 160 16 /133 /ACO	
		2	4717	2671	1688	1015	722	30,0	12,8							
		3	6724	3808	2406	1447	1030	46,4	19,6							
200	11	1	4423	2505	1582	952	741	26,0	13,4	1613	1927	STRW.035 200 11 /133 /ACO				
		2	4821	2730	1725	1037	807	30,0	14,8							
		3	6270	3551	2243	1349	1050	46,5	24,0							
	16	1	5667	3210	2028	1220	868	26,0	13,2				1947	2261	STRW.035 200 16 /133 /ACO	
		2	5971	3382	2137	1285	914	30,0	14,7							
		3	8618	4881	3083	1855	1320	47,1	23,5							
240	11	1	5238	2967	1874	1127	877	26,0	14,8	1997	2311	STRW.035 240 11 /133 /ACO				
		2	5738	3250	2053	1235	961	30,0	16,6							
		3	7648	4331	2736	1646	1281	47,2	28,0							
	16	1	6916	3917	2475	1488	1059	26,0	16,4				2431	2744	STRW.035 240 16 /133 /ACO	
		2	7168	4060	2565	1543	1098	30,0	17,7							
		3	10512	5953	3761	2262	1610	48,1	29,7							
280	11	1	5977	3385	2138	1286	956	26,0	16,2	2179	2492	STRW.035 280 11 /133 /ACO				
		2	6599	3737	2361	1420	1056	30,0	18,6							
		3	8790	4978	3145	1892	1406	47,8	31,4							
	16	1	8166	4625	2922	1757	1250	26,0	19,3				2688	3001	STRW.035 280 16 /133 /ACO	
		2	8348	4728	2987	1797	1278	30,0	20,4							
		3	12406	7026	4439	2670	1900	48,9	34,5							

OUTPUT EXPLANATION

HEATING CAPACITY
Due to the perfect combination of the DBH system and the extremely powerful Low-H₂O coil, the heater's height no longer influences the heat capacity. Thanks to the DBH system, maximum output is available for even the smallest heaters!

COOLING CAPACITY
The cooling capacity remains constant for all types with a maximum height of 50 cm. If the height exceeds 50 cm, the cooling capacity for types 11, 16 and 21 is reduced by approximately 5% for each additional 10 cm of height.

Output measured in accordance with EN 16430

Standard colour: **133** (traffic white RAL 9016)
or **001** (sandblast grey)
Other colours see Jaga colour chart

OUTPUTS STRADA HYBRID

HEIGHT 050

DIMENSIONS			POSITION	HEATING Room temperature 20°C				COOLING Room temperature 27°C	SOUND PRESSURE dB(A)	ELECTRIC POWER CONSUMPTION W	PRICE Standard colours €	PRICE Other colours €	ORDER CODE
H cm	L cm	B cm		75/65 Watts	55/45 Watts	45/35 Watts	35/30 Watts	16/18 Watts					
050	060	11	1	1142	647	409	246	191	26.0	4.8	742	855	STRW.050 060 11 /133 /ACO
			2	1223	693	438	263	205	30.0	5.4			
			3	1447	819	518	311	242	40.0	6.8			
	16	1	1400	793	501	301	214	26.0	4.8	818	931	STRW.050 060 16 /133 /ACO	
		2	1503	851	538	323	230	30.0	5.5				
		3	1989	1126	712	428	305	41.1	7.2				
080	11	11	1	1648	933	589	355	276	26.0	6.3	840	953	STRW.050 080 11 /133 /ACO
			2	1770	1002	633	381	296	30.0	6.8			
			3	2136	1210	764	460	358	41.8	9.1			
	16	1	2040	1156	730	439	312	26.0	6.0	945	1058	STRW.050 080 16 /133 /ACO	
		2	2188	1239	783	471	335	30.0	6.7				
		3	2936	1663	1050	632	450	42.4	9.0				
100	11	11	1	2136	1210	764	460	358	26.0	7.8	989	1168	STRW.050 100 11 /133 /ACO
			2	2301	1303	823	495	385	30.0	8.7			
			3	2825	1600	1011	608	473	43.0	12.2			
	16	1	2630	1490	941	566	403	26.0	7.0	1135	1315	STRW.050 100 16 /133 /ACO	
		2	2817	1595	1008	606	431	30.0	7.7				
		3	3883	2199	1389	836	595	44.1	10.7				
120	11	11	1	2612	1479	935	562	437	26.0	8.9	1087	1267	STRW.050 120 11 /133 /ACO
			2	2822	1598	1010	607	473	30.0	9.9			
			3	3514	1990	1257	756	589	44.0	14.8			
	16	1	3242	1836	1160	698	496	26.0	8.7	1254	1434	STRW.050 120 16 /133 /ACO	
		2	3472	1966	1242	747	532	30.0	9.8				
		3	4830	2735	1728	1039	740	44.8	14.3				
140	11	11	1	3077	1743	1101	662	515	26.0	10.1	1186	1365	STRW.050 140 11 /133 /ACO
			2	3333	1887	1192	717	558	30.0	11.2			
			3	4203	2380	1504	904	704	44.8	17.5			
	16	1	3844	2177	1376	827	589	26.0	9.6	1370	1549	STRW.050 140 16 /133 /ACO	
		2	4117	2332	1473	886	630	30.0	10.5				
		3	5777	3272	2067	1243	885	45.4	14.4				
160	11	11	1	3533	2001	1264	760	592	26.0	11.0	1440	1620	STRW.050 160 11 /133 /ACO
			2	3835	2172	1372	825	642	30.0	12.4			
			3	4892	2771	1750	1053	819	45.5	19.2			
	16	1	4418	2502	1581	951	676	26.0	11.5	1685	1864	STRW.050 160 16 /133 /ACO	
		2	4717	2671	1688	1015	722	30.0	12.8				
		3	6724	3808	2406	1447	1030	46.4	19.6				
200	11	11	1	4423	2505	1582	952	741	26.0	13.4	1655	1968	STRW.050 200 11 /133 /ACO
			2	4821	2730	1725	1037	807	30.0	14.8			
			3	6270	3551	2243	1349	1050	46.5	24.0			
	16	1	5667	3210	2028	1220	868	26.0	13.2	1990	2303	STRW.050 200 16 /133 /ACO	
		2	5971	3382	2137	1285	914	30.0	14.7				
		3	8618	4881	3083	1855	1320	47.1	23.5				
240	11	11	1	5238	2967	1874	1127	877	26.0	14.8	2047	2360	STRW.050 240 11 /133 /ACO
			2	5738	3250	2053	1235	961	30.0	16.6			
			3	7648	4331	2736	1646	1281	47.2	28.0			
	16	1	6916	3917	2475	1488	1059	26.0	16.4	2482	2795	STRW.050 240 16 /133 /ACO	
		2	7168	4060	2565	1543	1098	30.0	17.7				
		3	10512	5953	3761	2262	1610	48.1	29.7				
280	11	11	1	5977	3385	2138	1286	956	26.0	16.2	2235	2548	STRW.050 280 11 /133 /ACO
			2	6599	3737	2361	1420	1056	30.0	18.6			
			3	8790	4978	3145	1892	1406	47.8	31.4			
	16	1	8166	4625	2922	1757	1250	26.0	19.3	2746	3060	STRW.050 280 16 /133 /ACO	
		2	8348	4728	2987	1797	1278	30.0	20.4				
		3	12406	7026	4439	2670	1900	48.9	34.5				

OUTPUT EXPLANATION

HEATING CAPACITY
Due to the perfect combination of the DBH system and the extremely powerful Low-H₂O coil, the heater's height no longer influences the heat capacity. Thanks to the DBH system, maximum output is available for even the smallest heaters!

COOLING CAPACITY
The cooling capacity remains constant for all types with a maximum height of 50 cm. If the height exceeds 50 cm, the cooling capacity for types 11, 16 and 21 is reduced by approximately 5% for each additional 10 cm of height.

Output measured in accordance with EN 16430

Standard colour: 133 (traffic white RAL 9016)
or 001 (sandblast grey)
Other colours see Jaga colour chart

OUTPUTS STRADA HYBRID

HEIGHT 065

DIMENSIONS			POSITION	HEATING Room temperature 20°C				COOLING Room temperature 27°C	SOUND PRESSURE	ELECTRIC POWER CONSUMPTION	PRICE Standard colours	PRICE Other colours	ORDER CODE			
H	L	B		75/65	55/45	45/35	35/30	16/18								
cm	cm	cm		Watts	Watts	Watts	Watts	Watts	dB(A)	W	€	€				
065	060	11	1	1142	647	409	246	177	26.0	4.8	762	875	STRW.065 060 11 /133 /ACO			
			2	1223	693	438	263	189	30.0	5.4						
			3	1447	819	518	311	224	40.0	6.8						
		16	1	1400	793	501	301	198	26.0	4.8				845	958	STRW.065 060 16 /133 /ACO
			2	1503	851	538	323	213	30.0	5.5						
			3	1989	1126	712	428	282	41.1	7.2						
	080	11	1	1648	933	589	355	255	26.0	6.3	863	976	STRW.065 080 11 /133 /ACO			
			2	1770	1002	633	381	274	30.0	6.8						
			3	2136	1210	764	460	331	41.8	9.1						
		16	1	2040	1156	730	439	289	26.0	6.0				973	1086	STRW.065 080 16 /133 /ACO
			2	2188	1239	783	471	310	30.0	6.7						
			3	2936	1663	1050	632	416	42.4	9.0						
	100	11	1	2136	1210	764	460	331	26.0	7.8	1013	1192	STRW.065 100 11 /133 /ACO			
			2	2301	1303	823	495	357	30.0	8.7						
			3	2825	1600	1011	608	438	43.0	12.2						
		16	1	2630	1490	941	566	373	26.0	7.0				1163	1343	STRW.065 100 16 /133 /ACO
			2	2817	1595	1008	606	399	30.0	7.7						
			3	3883	2199	1389	836	550	44.1	10.7						
	120	11	1	2612	1479	935	562	405	26.0	8.9	1117	1297	STRW.065 120 11 /133 /ACO			
			2	2822	1598	1010	607	437	30.0	9.9						
			3	3514	1990	1257	756	544	44.0	14.8						
		16	1	3242	1836	1160	698	459	26.0	8.7				1288	1467	STRW.065 120 16 /133 /ACO
			2	3472	1966	1242	747	492	30.0	9.8						
			3	4830	2735	1728	1039	684	44.8	14.3						
140	11	1	3077	1743	1101	662	477	26.0	10.1	1219	1399	STRW.065 140 11 /133 /ACO				
		2	3333	1887	1192	717	516	30.0	11.2							
		3	4203	2380	1504	904	651	44.8	17.5							
	16	1	3844	2177	1376	827	544	26.0	9.6				1409	1588	STRW.065 140 16 /133 /ACO	
		2	4117	2332	1473	886	583	30.0	10.5							
		3	5777	3272	2067	1243	818	45.4	14.4							
160	11	1	3533	2001	1264	760	547	26.0	11.0	1478	1658	STRW.065 160 11 /133 /ACO				
		2	3835	2172	1372	825	594	30.0	12.4							
		3	4892	2771	1750	1053	758	45.5	19.2							
	16	1	4418	2502	1581	951	626	26.0	11.5				1728	1908	STRW.065 160 16 /133 /ACO	
		2	4717	2671	1688	1015	668	30.0	12.8							
		3	6724	3808	2406	1447	952	46.4	19.6							
200	11	1	4423	2505	1582	952	685	26.0	13.4	1697	2011	STRW.065 200 11 /133 /ACO				
		2	4821	2730	1725	1037	747	30.0	14.8							
		3	6270	3551	2243	1349	971	46.5	24.0							
	16	1	5667	3210	2028	1220	803	26.0	13.2				2039	2352	STRW.065 200 16 /133 /ACO	
		2	5971	3382	2137	1285	846	30.0	14.7							
		3	8618	4881	3083	1855	1221	47.1	23.5							
240	11	1	5238	2967	1874	1127	812	26.0	14.8	2099	2412	STRW.065 240 11 /133 /ACO				
		2	5738	3250	2053	1235	889	30.0	16.6							
		3	7648	4331	2736	1646	1185	47.2	28.0							
	16	1	6916	3917	2475	1488	980	26.0	16.4				2543	2856	STRW.065 240 16 /133 /ACO	
		2	7168	4060	2565	1543	1015	30.0	17.7							
		3	10512	5953	3761	2262	1489	48.1	29.7							
280	11	1	5977	3385	2138	1286	885	26.0	16.2	2294	2607	STRW.065 280 11 /133 /ACO				
		2	6599	3737	2361	1420	977	30.0	18.6							
		3	8790	4978	3145	1892	1301	47.8	31.4							
	16	1	8166	4625	2922	1757	1156	26.0	19.3				2812	3125	STRW.065 280 16 /133 /ACO	
		2	8348	4728	2987	1797	1182	30.0	20.4							
		3	12406	7026	4439	2670	1757	48.9	34.5							

OUTPUT EXPLANATION

HEATING CAPACITY
Due to the perfect combination of the DBH system and the extremely powerful Low-H₂O coil, the heater's height no longer influences the heat capacity. Thanks to the DBH system, maximum output is available for even the smallest heaters!

COOLING CAPACITY
The cooling capacity remains constant for all types with a maximum height of 50 cm. If the height exceeds 50 cm, the cooling capacity for types 11, 16 and 21 is reduced by approximately 5% for each additional 10 cm of height.

Output measured in accordance with EN 16430

Standard colour: 133 (traffic white RAL 9016) or 001 (sandblast grey)
Other colours see Inga colour chart

OUTPUTS STRADA HYBRID

HEIGHT 095

DIMENSIONS			POSITION	HEATING Room temperature 20°C				COOLING Room temperature 27°C		SOUND PRESSURE dB(A)	ELECTRIC POWER CONSUMPTION W	PRICE Standard colours €	PRICE Other colours €	ORDER CODE
H cm	L cm	B cm		75/65 Watts	55/45 Watts	45/35 Watts	35/30 Watts	16/18 Watts						
095	060	11	1	1142	647	409	246	148	26.0	4.8	791	904	STRW.095 060 11 /133 /ACO	
			2	1223	693	438	263	159	30.0	5.4				
			3	1447	819	518	311	188	40.0	6.8				
	16	1	1400	793	501	301	166	26.0	4.8	879	992	STRW.095 060 16 /133 /ACO		
		2	1503	851	538	323	178	30.0	5.5					
		3	1989	1126	712	428	236	41.1	7.2					
080	11	11	1	1648	933	589	355	214	26.0	6.3	896	1009	STRW.095 080 11 /133 /ACO	
			2	1770	1002	633	381	230	30.0	6.8				
			3	2136	1210	764	460	277	41.8	9.1				
	16	1	2040	1156	730	439	242	26.0	6.0	1015	1128	STRW.095 080 16 /133 /ACO		
		2	2188	1239	783	471	260	30.0	6.7					
		3	2936	1663	1050	632	348	42.4	9.0					
100	11	11	1	2136	1210	764	460	277	26.0	7.8	1057	1237	STRW.095 100 11 /133 /ACO	
			2	2301	1303	823	495	299	30.0	8.7				
			3	2825	1600	1011	608	367	43.0	12.2				
	16	1	2630	1490	941	566	312	26.0	7.0	1216	1395	STRW.095 100 16 /133 /ACO		
		2	2817	1595	1008	606	334	30.0	7.7					
		3	3883	2199	1389	836	461	44.1	10.7					
120	11	11	1	2612	1479	935	562	339	26.0	8.9	1167	1347	STRW.095 120 11 /133 /ACO	
			2	2822	1598	1010	607	366	30.0	9.9				
			3	3514	1990	1257	756	456	44.0	14.8				
	16	1	3242	1836	1160	698	385	26.0	8.7	1347	1526	STRW.095 120 16 /133 /ACO		
		2	3472	1966	1242	747	412	30.0	9.8					
		3	4830	2735	1728	1039	573	44.8	14.3					
140	11	11	1	3077	1743	1101	662	399	26.0	10.1	1280	1460	STRW.095 140 11 /133 /ACO	
			2	3333	1887	1192	717	433	30.0	11.2				
			3	4203	2380	1504	904	546	44.8	17.5				
	16	1	3844	2177	1376	827	456	26.0	9.6	1479	1659	STRW.095 140 16 /133 /ACO		
		2	4117	2332	1473	886	489	30.0	10.5					
		3	5777	3272	2067	1243	685	45.4	14.4					

OUTPUT EXPLANATION

HEATING CAPACITY
Due to the perfect combination of the DBH system and the extremely powerful Low-H₂O coil, the heater's height no longer influences the heat capacity. Thanks to the DBH system, maximum output is available for even the smallest heaters!

COOLING CAPACITY
The cooling capacity remains constant for all types with a maximum height of 50 cm. If the height exceeds 50 cm, the cooling capacity for types 11, 16 and 21 is reduced by approximately 5% for each additional 10 cm of height.

Output measured in accordance with EN 16430

Standard colour: **133** (traffic white RAL 9016)
or **001** (sandblast grey)
Other colours see Jaga colour chart